

2009

## On an approach to provide space diversity to an ultra wideband time hopping pulse position modulated wireless communication system

Peter Vial

*University of Wollongong*, [peter.v@uow.edu.au](mailto:peter.v@uow.edu.au)

Follow this and additional works at: <https://ro.uow.edu.au/theses>

### University of Wollongong

#### Copyright Warning

You may print or download ONE copy of this document for the purpose of your own research or study. The University does not authorise you to copy, communicate or otherwise make available electronically to any other person any copyright material contained on this site.

You are reminded of the following: This work is copyright. Apart from any use permitted under the Copyright Act 1968, no part of this work may be reproduced by any process, nor may any other exclusive right be exercised, without the permission of the author. Copyright owners are entitled to take legal action against persons who infringe their copyright. A reproduction of material that is protected by copyright may be a copyright infringement. A court may impose penalties and award damages in relation to offences and infringements relating to copyright material.

Higher penalties may apply, and higher damages may be awarded, for offences and infringements involving the conversion of material into digital or electronic form.

Unless otherwise indicated, the views expressed in this thesis are those of the author and do not necessarily represent the views of the University of Wollongong.

### Recommended Citation

Vial, Peter J, On an approach to provide space diversity to an ultra wideband time hopping pulse position modulated wireless communication system, PhD thesis, School of Electrical, Computer and Telecommunications Engineering, University of Wollongong, 2009. <http://ro.uow.edu.au/theses/811>

## **NOTE**

This online version of the thesis may have different page formatting and pagination from the paper copy held in the University of Wollongong Library.

## **UNIVERSITY OF WOLLONGONG**

### **COPYRIGHT WARNING**

You may print or download ONE copy of this document for the purpose of your own research or study. The University does not authorise you to copy, communicate or otherwise make available electronically to any other person any copyright material contained on this site. You are reminded of the following:

Copyright owners are entitled to take legal action against persons who infringe their copyright. A reproduction of material that is protected by copyright may be a copyright infringement. A court may impose penalties and award damages in relation to offences and infringements relating to copyright material. Higher penalties may apply, and higher damages may be awarded, for offences and infringements involving the conversion of material into digital or electronic form.

**On an approach to provide space diversity to an Ultra Wideband  
Time Hopping Pulse Position Modulated wireless communication  
system.**

**Doctor Of Philosophy (PhD)**

**from**

**UNIVERSITY OF WOLLONGONG**

**by**

**Peter James Vial,  
BE (Hons 2 (i)), ME (Hons), DipEd**

**School of Electrical, Computer and  
Telecommunications Engineering**

**2009**

## Abstract

The hypothesis question, which is addressed in this PhD dissertation, is how to use two transmission antennas in an Ultra Wide Band Time Hopping Pulse Position Modulation system to take advantage of space diversity in such a way as to not significantly degrade the communication link compared to using only one transmit antenna. In answering the hypothesis question, this dissertation proposes a novel technique, based on Space Time Spreading, to allow an Ultra Wideband Time Hopping Pulse Position Modulation system to obtain full advantage from space diversity using two transmit antennas and one receive antenna, showing how such a Multiple Input Multiple Output system is designed. This is achieved with the added advantage of transmitting the same two symbols simultaneously on each antenna link. This means that for the proposed system, should a fade occur on one of the two antenna links, the two symbols transmitted will still be received with a slight increased cost in average Bit Error Rate (BER) performance as Signal to Noise Ratio (SNR) or measured  $E_b/N_0$  is increased.

Results are first provided for wideband Space Time Spreading in the presence of Multiple Access Interference when using two, four and eight transmit antennas. A system is developed in simulation using modules provided by MATLABs Simulink program. It is then shown that using low correlation Wysocki spreading code set results in an improved BER performance compared to the more often used Walsh Hadamard spreading code set. A Simulink Ultra Wide Band Pulse Position Modulation Single Input Single Output system is developed and validated against published peer reviewed material. This is then modified to consider the use of Space Time Spreading in a Single Input Single Output system and it is shown that improved performance over an Ultra Wide Band Pulse Position Modulated Single Input Single Output is possible. It is also shown that this improvement allows the transmission of two symbols in the same time that the original system only transmits one symbol.

The thesis also investigates a system which uses two transmit antennas but a hard decision is made on a chip by chip basis. Its performance, compared to an equivalent Single Input Single Output comparable system, is suboptimal. It does, however, have the advantage that it sends two symbols in the same time that the equivalent Single Input Single output Ultra Wide Band Pulse Position Modulation system sends one, and its implementation is simpler to codify. Also, it has the feature that both symbols are sent simultaneously on each antenna link.

The simulator is then modified to make a hard decision after all chips of a spreading sequence for two antennas are received and it is shown that this system, in simulation and analysis, has a similar performance to that for a comparable Single Input Single Output system with the added advantage that both antenna links send the same two symbols simultaneously. It is further demonstrated in simulation and analysis that such systems can be affected by Multiple Access Interference. In addition, it is shown, using simulation, that the choice of spreading sequence set does have an impact on the average BER performance of the proposed Space Time Spreading Time Hopping Ultra Wideband Pulse Position Modulation system. The thesis finally proposes some extensions using the developed simulator which are outlined in future work.

## Statement of Originality

I Peter James Vial swear that this thesis, where attribute is not given to others, is solely my work and my research and no others. I personally wrote all the code or made modifications to existing code where attribution is provided via the codes comments, developed the proposed systems and undertook all associated studies including the analysis of the proposed system.

Signed: Mr Peter James Vial

Dated: 21<sup>st</sup> of May 2009

## Acknowledgements

I wish to acknowledge all my supervisors who have assisted me in this work over the course of my studies. In particular Professor Tad Wysocki who started me on this path and who was my direct supervisor for most of my candidature for a PhD, Dr Beata Wysocki who helped and assisted with the published material and provided encouragement, Dr David Stirling for assisting at the end of my candidature with Dr Montse Ros, and my other two co-supervisors Dr Philip Ciufo and Professor Salim Bouzerdoun who were involved for brief periods of time in my candidature. I also acknowledge the assistance provided in Buffalo (New York, USA) by Dr Kylie Keshav (aka MacKenzie) who advised me on aspects of my PhD layout and who suggested the use of Reference Manager for the referencing as an alternative to that provided directly by Word 2007 (which does not provide correct IEEE referencing).

I would also like to acknowledge my family and friends who provided assistance while I undertook this study. My father, Dr Kenneth J Vial, who encouraged me to pursue academic matters when he was alive. My mother, Dr Denise Wallis, who has also encouraged me in my studies over these many years. My parents in law, Marie and Brian Bourke who have provided support and assistance when needed, especially with my children as they have grown up. My children John Francis Steven Vial and Alanna Heather-Therese Vial who have provided many hours of entertaining conversation. Finally, in particular, my wife Mrs Kathrine Anne Vial who provided loving support and encouragement while I made a significant contribution to the area of UWB communications. Without Kathrine this thesis would not have been possible.

## Peer reviewed Publications of this thesis

- [1] P. Vial, I. Raad, and T. Wysocki, "On the effect of adjacent sector Multiple Access Interference on Space Time Spreading Systems," in *Conference Proceedings of DSPCS'03*, Coolangatta, Queensland, Australia, pp. 543-548, December, 2003.
- [2] P. J. Vial, I. S. Raad, and T. A. Wysocki, "On the Design and Validation of a Space Time Spreading System using Simulink," in *Conference Proceedings of the 14th International Czech-Slovak Scientific Conference Radioelektronika*, Bratislava, Slovak Republic, pp. 480-483, April, 2004.
- [3] P. Vial, B. Wysocki, I. Raad, and T. Wysocki, "Space time spreading with modified Walsh-Hadamard sequences," in *Conference Proceedings of the Eighth IEEE International Symposium on Spread Spectrum Techniques and Applications*, Sydney, Australia, pp. 943-946, August, 2004.
- [4] P. Vial, B. Wysocki, and T. Wysocki, "An Ultra Wideband Simulator Using MATLAB / Simulink," in *Conference Proceedings of DSPCS'05 & WITSP'05*, Noosa Heads, Queensland, Australia, December, 2005.
- [5] P. Vial, B. Wysocki, and T. Wysocki, "Direct Sequence Modified Time Hopping PPM over Ultra Wideband S-V Channel," in *Conference Proceedings of the 5th Workshop on the Internet, telecommunications and Signal Processing (WITSP'06)*, Hobart, Tasmania, Australia, December, 2006.
- [6] P. Vial, B. Wysocki, and T. Wysocki, "Optimal receiver for Space Time Spreading across a Time Hopping PPM over Ultra Wideband Saleh-Valenzuela MIMO Channel," in *Conference Proceedings of the International Conference on Signal Processing and Communication Systems, 2007 (ICSPCS '2007)*, Gold Coast, Queensland, Australia, pp. 56-61, December, 2007.
- [7] P. Vial, B. Wysocki, and T. A. Wysocki, "Non-optimal receiver for space time spreading across a Time Hopping over Ultra Wideband PPM," in *Conference Proceedings of the third International Symposium on Communications, Control and Signal Processing, 2008 (ISCCSP 2008)*, Malta, pp. 990-993, March, 2008.



P. Vial, B. Wysocki, M. Ros, T.A. Wysocki, and D. Stirling, “On the effect of Multiple Access Interference in a Space Time Spreading Time Hopping PPM UWB System”, submitted to IEEE Transactions on Wireless Communications on the 5<sup>th</sup> of February 2009.

## Table of Contents

Abstract .....	ii
Statement of Originality .....	iv
Acknowledgements .....	v
Peer reviewed Publications of this thesis.....	vi
Submitted to Journal for peer reviewed Publication .....	vii
List of Figures.....	xvi
List of Tables .....	xx
List of Abbreviations.....	xxi
Chapter 1: Introduction.....	1
1.1 Introduction.....	1
1.2 Research Questions .....	2
1.3 Contributions of this thesis .....	3
1.4 Outline of this thesis.....	6
Chapter 2: Literature Review .....	8
2.1 Introduction.....	8
2.2 MIMO and block orthogonal codes.....	8
2.3 MIMO and Block coding with Quasi-orthogonal codes.....	13
2.4 Alamouti on simple transmit diversity .....	16
2.5 Wideband CDMA systems based on Space Time Spreading .....	21
2.6 A Brief description of other works on Space Time Techniques.....	39
2.7 Ultra Wideband Systems .....	41
2.8 Multiband Orthogonal frequency division multiplexing .....	42
2.9 Ultra Wideband Pulse Position Modulation SISO systems.....	45
2.10 Ultra Wideband Pulse Position Modulation MIMO systems.....	49
2.11 The Saleh-Valenzuela multipath channel .....	67
2.12 Methodology .....	77
2.13 Conclusion .....	78
Chapter 3: Modeling and Validation of STS system in Simulink.....	79
3.1 Introduction.....	79
3.2 Space Time Spreading.....	80
3.3 Description and Design of Model .....	82

3.4	Validation of SIMULINK model .....	90
3.5	Observations.....	93
3.6	Conclusion .....	94
Chapter 4:	Multiple Access Interference in STS systems .....	95
4.1	Introduction .....	95
4.2	Description of SIMULINK model .....	97
4.3	Adjacent Multiple Access Interference (MAI) .....	97
4.4	Effect of Adjacent MAI.....	99
4.5	On the effect of low correlation codes on MAI in STS .....	101
4.6	Improved Orthogonal Codes .....	101
4.7	Simulation results using improved orthogonal codes .....	101
4.8	Conclusion .....	103
Chapter 5:	Simulation and Validation of a SISO UWB-PPM system using Simulink .....	105
5.1	Introduction .....	105
5.2	UWB Signals and the Saleh-Valenzuela multipath Channel .....	106
5.3	Channel Definition and modeling.....	110
5.4	Design of Simulink UWB-PPM Model .....	111
5.5	Model Validation .....	112
5.6	Conclusion .....	117
Chapter 6:	DS Modified TH PPM over UWB SISO S-V Channel .....	119
6.1	Introduction .....	119
6.2	DS-TH-UWB with Two pulse Positions.....	121
6.3	DS Modified-TH Pulse Position Modulation .....	122
6.4	Comparison of DS-TH-UWB with DS-Modified-TH-UWB.....	124
6.5	Conclusion .....	127
Chapter 7:	Non-Optimal receiver for STS - TH over UWB PPM MIMO S-V Channel .....	128
7.1	Introduction .....	128
7.2	DS-TH-UWB with two pulse positions .....	130
7.3	MIMO system .....	131
7.4	Measured $E_b/N_o$ for MIMO system.....	134
7.5	Comparison of MIMO and SISO .....	135
7.6	Conclusion .....	138
Chapter 8:	Optimal receiver for STS across a TH PPM over UWB S-V MIMO Channel .....	140
8.1	Introduction .....	140

8.2	Yang's Analog ST coding I scheme .....	142
8.3	STS-TH-UWB-PPM system .....	143
8.4	Simulation of Yang's Analog ST coding I .....	146
8.5	Comparison with STS system .....	147
8.6	Conclusion .....	151
Chapter 9:	MAI in STS-TH-UWB-PPM systems .....	152
9.1	Introduction .....	152
9.2	Modifications to STS-TH-UWB-PPM system .....	153
9.3	MAI in STS-TH-UWB-PPM system .....	154
9.4	MAI in STS-TH-UWB-PPM results using Walsh-Hadamard codes .....	155
9.5	MAI using low correlation sequences .....	164
9.6	Conclusion .....	172
Chapter 10:	Analysis of STS-TH-UWB-PPM system for All Rake in presence of MAI .....	174
10.1	Introduction .....	174
10.2	Description of System parameters .....	174
10.3	The STS-TH-UWB-PPM demodulator .....	180
10.4	The average BER in the presence and absence of MAI .....	186
10.5	The average SER versus SNR for All Rake .....	196
10.6	Conclusion .....	200
Chapter 11:	Conclusion .....	201
11.1	Introduction .....	201
11.2	Significant Contributions of the thesis .....	201
11.3	Future Work .....	205
References	.....	208
Appendix 1:	Utility MATLAB scripts used in study for plotting .....	217
	MATLAB script: errorBars_utility.m .....	217
	MATLAB script: calculate_area_under_positive_curve.m .....	218
Appendix 2:	STS Simulink results for m=4, 8 tabulated data .....	219
	STS for Four Transmit Antennas .....	219
	STS for Eight Transmit Antennas .....	220
Appendix 3:	MAI in STS tabulated data .....	221
	Case study 1: Single MAI interferer – Walsh-Hadamard for 0dB .....	221
	Case study 2: Two MAI interferers – Walsh-Hadamard for 0dB .....	222
	Case study 3: One MAI interferers – Walsh-Hadamard for 4dB .....	223

Appendix 4: MAI in STS 95% confidence intervals tabulated data for low correlation codes .....	224
Case study 1: Single MAI interferer – alternating pairs of orthogonal 32 chip low correlation codes .....	224
Case study 2: Single MAI interferer one set only of 32 chip low correlation code pairs used .....	225
Appendix 5: MATLAB script to generate STS wideband system plot for m=1, 2, 4 and 8 .....	226
MATLAB script: mequals124and8resultsforstsinPhdappendix.m .....	226
Appendix 6: MATLAB scripts to generate SV channel matrices .....	228
MATLAB script: cp0802_IIEEuwbpvialsv.m .....	228
MATLAB script: createinputdatavectors.m .....	238
MATLAB script: createSDTotal.m .....	244
Appendix 7: UWB PPM with 95% confidence intervals tabulated data for validation simulations .....	245
UWB PPM L=1 First Useful arriving ray (Partial Rake) Simulink simulation data .....	245
UWB PPM L=4 First Useful arriving ray (Partial Rake) Simulink simulation data .....	246
Appendix 8: UWB PPM with 95% confidence intervals tabulated data for first arriving rays and best arriving rays (Selective Rake) .....	247
UWB PPM L=1 First arriving ray Simulink simulation data .....	247
UWB PPM L=4 First four arriving rays Simulink simulation data .....	247
UWB PPM L=1 best arriving ray (Selective Rake) Simulink simulation data .....	248
UWB PPM L=4 best arriving ray (Selective Rake) Simulink simulation data .....	248
Appendix 9: DS TH UWB PPM with 95% confidence intervals tabulated data for first arriving rays (Partial Rake) and best arriving rays (Selective Rake) .....	249
DS TH UWB PPM two pulse system for Partial Rake, L=1 .....	249
DS TH UWB PPM two pulse system for Partial Rake, L=4 .....	249
DS TH UWB PPM two pulse system Selective Rake, L=1 .....	250
DS TH UWB PPM two pulse system Selective Rake, L=4 .....	250
Appendix 10: DS Modified TH UWB PPM with 95% confidence intervals tabulated data for first arriving rays (Partial Rake) and best arriving rays (Selective Rake) .....	251
DS Modified TH UWB PPM three pulse system for Partial Rake, L=1 .....	251
DS Modified TH UWB PPM three pulse system for Partial Rake, L=4 .....	251
DS Modified TH UWB PPM three pulse system Selective Rake, L=1 .....	252
DS Modified TH UWB PPM three pulse system Selective Rake, L=4 .....	252
Appendix 11: Single seed data (seedc) for SISO DS TH UWB PPM for first rays, for first useful arriving rays (Partial Rake) and best arriving rays (Selective Rake) .....	253
DS TH UWB PPM two pulse system for first arriving ray, L=1 .....	253
DS TH UWB PPM two pulse system for first four arriving rays, L=4 .....	253
DS TH UWB PPM two pulse system for first useful arriving rays (PRake), L=1 .....	254

DS TH UWB PPM two pulse system for first four useful arriving rays (PRake), L=4 .....	254
DS TH UWB PPM two pulse system for best useful arriving rays (SRake), L=1 .....	255
DS TH UWB PPM two pulse system for best four useful arriving rays (PRake), L=4 .....	255
Appendix 12: Single seed data (seedc) for MIMO Non-Optimal STS TH UWB PPM (chip by chip decision) for first rays, for first useful arriving rays (Partial Rake) and best arriving rays (Selective Rake) .....	256
MIMO Non-optimal STS TH UWB PPM two pulse system for first arriving ray, L=1 .....	256
MIMO Non-optimal STS TH UWB PPM two pulse system for first four arriving rays, L=4.....	257
MIMO Non-optimal STS TH UWB PPM two pulse system for first useful arriving rays (PRake), L=1 .....	258
MIMO Non-optimal STS TH UWB PPM two pulse system for first four useful arriving rays (PRake), L=4.....	259
MIMO Non-optimal STS TH UWB PPM two pulse system for best useful arriving rays (SRake), L=1 .....	260
MIMO Non-optimal STS TH UWB PPM two pulse system for best four useful arriving rays (PRake), L=4 .....	261
Appendix 13: MIMO DS UWB PPM with 95% confidence intervals tabulated data for validation simulations of Yang Analog ST coding I schema from Yang [9].....	262
MIMO DS UWB PPM L=1 First Useful arriving ray (Partial Rake) Simulink simulation data.....	262
MIMO DS UWB PPM L=4 First Useful arriving ray (Partial Rake) Simulink simulation data.....	262
MIMO DS UWB PPM L=1 best Useful arriving ray (Selective Rake) Simulink simulation data.....	263
MIMO DS UWB PPM L=4 best four Useful arriving rays (Selective Rake) Simulink simulation data .....	263
Appendix 14: MIMO DS UWB PPM with 95% confidence intervals tabulated data for validation simulations of Yang Analog ST coding I schema from Yang [9] in terms of measured Eb/No .....	264
MIMO DS UWB PPM L=1 First Useful arriving ray (Partial Rake) Simulink simulation data for measured Eb/No .....	264
MIMO DS UWB PPM L=4 First Useful arriving ray (Partial Rake) Simulink simulation data for measured Eb/No .....	264
MIMO DS UWB PPM L=1 best Useful arriving ray (Selective Rake) Simulink simulation data for measured Eb/No.....	265
MIMO DS UWB PPM L=4 best four Useful arriving rays (Selective Rake) Simulink simulation data for measured Eb/No.....	265
Appendix 15: Optimal MIMO STS TH UWB PPM with 95% confidence intervals tabulated data in terms of measured Eb/No.....	266
MIMO STS TH UWB PPM L=1 First Useful arriving ray (Partial Rake) Simulink simulation data for measured Eb/No.....	266
MIMO STS TH UWB PPM L=4 First four Useful arriving rays (Partial Rake) Simulink simulation data for measured Eb/No.....	267
MIMO STS TH UWB PPM L=1 best Useful arriving ray (Selective Rake) Simulink simulation data for measured Eb/No.....	268
MIMO STS TH UWB PPM L=4 best four Useful arriving rays (Selective Rake) Simulink simulation data for measured Eb/No.....	269

Appendix 16: Optimal MIMO STS TH UWB PPM with 95% confidence intervals tabulated data in terms of measured Eb/No adjusted for two symbols and one branch as each branch has both transmitted symbols ...	270
MIMO STS TH UWB PPM L=1 First Useful arriving ray (Partial Rake) Simulink simulation data for measured Eb/No.....	270
MIMO STS TH UWB PPM L=4 First four Useful arriving rays (Partial Rake) Simulink simulation data for measured Eb/No.....	271
MIMO STS TH UWB PPM L=1 best Useful arriving ray (Selective Rake) Simulink simulation data for measured Eb/No.....	272
MIMO STS TH UWB PPM L=4 best four Useful arriving rays (Selective Rake) Simulink simulation data for measured Eb/No.....	273
Appendix 17: Optimal MIMO STS TH UWB PPM in presence of MAI using 32 chip Walsh Hadamard spreading sequences with 95% confidence intervals tabulated data .....	274
Table of Walsh Hadamard Code set assignments for 10 MAI case study .....	274
MIMO STS TH UWB PPM L=1 using 32 chip Walsh Hadamard spreading sequences First useful arriving ray (Partial Rake) Simulink simulation data for measured Eb/No in presence of 5 MAI at measured Eb/No of 3.15dB.....	275
MIMO STS TH UWB PPM L=4 using 32 chip Walsh Hadamard spreading sequences First four useful arriving rays (Partial Rake) Simulink simulation data for measured Eb/No in presence of 5 MAI at measured Eb/No of 3.15dB.....	275
MIMO STS TH UWB PPM L=1 using 32 chip Walsh Hadamard spreading sequences First useful arriving ray (Partial Rake) Simulink simulation data for measured Eb/No in presence of 10 MAI at measured Eb/No of 3.15dB.....	276
MIMO STS TH UWB PPM L=4 using 32 chip Walsh Hadamard spreading sequences First four useful arriving rays (Partial Rake) Simulink simulation data for measured Eb/No in presence of 10 MAI at measured Eb/No of 3.15dB .....	276
Appendix 18: Optimal MIMO STS TH UWB PPM in presence of MAI using 32 chip Wysocki (low cross-correlation) spreading sequences with 95% confidence intervals tabulated data .....	277
Table of Wysocki Code set assignments for 10 MAI case study.....	277
MIMO STS TH UWB PPM L=1 using 32 chip Wysocki (low cross-correlation) spreading sequences First useful arriving ray (Partial Rake) Simulink simulation data for measured Eb/No in presence of 5 MAI at measured Eb/No of 3.15dB .....	278
MIMO STS TH UWB PPM L=4 using 32 chip Wysocki (low cross-correlation) spreading sequences First four useful arriving rays (Partial Rake) Simulink simulation data for measured Eb/No in presence of 5 MAI at measured Eb/No of 3.15dB .....	278
MIMO STS TH UWB PPM L=1 using 32 chip Wysocki (low cross-correlation) spreading sequences First useful arriving ray (Partial Rake) Simulink simulation data for measured Eb/No in presence of 10 MAI at measured Eb/No of 3.15dB .....	279
MIMO STS TH UWB PPM L=4 using 32 chip Wysocki (low cross-correlation) spreading sequences First four useful arriving rays (Partial Rake) Simulink simulation data for measured Eb/No in presence of 10 MAI at measured Eb/No of 3.15dB .....	279

Appendix 19: Optimal MIMO STS TH UWB PPM in presence of MAI using 32 chip Gold orthogonal spreading sequences with 95% confidence intervals tabulated data .....	280
Table of Gold orthogonal Code set assignments for 10 MAI case study.....	280
MIMO STS TH UWB PPM L=1 using 32 chip gold (low cross-correlation) spreading sequences First useful arriving ray (Partial Rake) Simulink simulation data for measured Eb/No in presence of 5 MAI at measured Eb/No of 3.15dB .....	281
MIMO STS TH UWB PPM L=4 using 32 chip gold (low cross-correlation) spreading sequences First four useful arriving rays (Partial Rake) Simulink simulation data for measured Eb/No in presence of 5 MAI at measured Eb/No of 3.15dB .....	281
MIMO STS TH UWB PPM L=1 using 32 chip gold (low cross-correlation) spreading sequences First useful arriving ray (Partial Rake) Simulink simulation data for measured Eb/No in presence of 10 MAI at measured Eb/No of 3.15dB .....	282
MIMO STS TH UWB PPM L=4 using 32 chip gold (low cross-correlation) spreading sequences First four useful arriving rays (Partial Rake) Simulink simulation data for measured Eb/No in presence of 10 MAI at measured Eb/No of 3.15dB .....	282
Appendix 20: Optimal MIMO STS TH UWB PPM in presence of MAI using 32 chip w32dash03 low correlation orthogonal spreading sequences with 95% confidence intervals tabulated data .....	283
Table of w32dash03 orthogonal Code set assignments for 10 MAI case study.....	283
MIMO STS TH UWB PPM L=1 using 32 chip w32dash03 (low cross-correlation) spreading sequences First useful arriving ray (Partial Rake) Simulink simulation data for measured Eb/No in presence of 5 MAI at measured Eb/No of 3.15dB .....	284
MIMO STS TH UWB PPM L=4 using 32 chip w32dash03 (low cross-correlation) spreading sequences First four useful arriving rays (Partial Rake) Simulink simulation data for measured Eb/No in presence of 5 MAI at measured Eb/No of 3.15dB .....	284
MIMO STS TH UWB PPM L=1 using 32 chip w32dash03 (low cross-correlation) spreading sequences First useful arriving ray (Partial Rake) Simulink simulation data for measured Eb/No in presence of 10 MAI at measured Eb/No of 3.15dB .....	285
MIMO STS TH UWB PPM L=4 using 32 chip w32dash03 (low cross-correlation) spreading sequences First four useful arriving rays (Partial Rake) Simulink simulation data for measured Eb/No in presence of 10 MAI at measured Eb/No of 3.15dB .....	285
Appendix 21: Optimal MIMO STS TH UWB PPM in presence of MAI using 32 chip h32dash03 orthogonal spreading sequences with 95% confidence intervals tabulated data .....	286
Table of h32dash03 orthogonal Code set assignments for 10 MAI case study .....	286
MIMO STS TH UWB PPM L=1 using 32 chip h32dash03 spreading sequences First useful arriving ray (Partial Rake) Simulink simulation data for measured Eb/No in presence of 5 MAI at measured Eb/No of 3.15dB ..	287
MIMO STS TH UWB PPM L=4 using 32 chip h32dash03 spreading sequences First four useful arriving rays (Partial Rake) Simulink simulation data for measured Eb/No in presence of 5 MAI at measured Eb/No of 3.15dB.....	287
MIMO STS TH UWB PPM L=1 using 32 chip h32dash03 spreading sequences First useful arriving ray (Partial Rake) Simulink simulation data for measured Eb/No in presence of 10 MAI at measured Eb/No of 3.15dB	288



MIMO STS TH UWB PPM L=4 using 32 chip h32dash03 spreading sequences First four useful arriving rays (Partial Rake) Simulink simulation data for measured Eb/No in presence of 10 MAI at measured Eb/No of 3.15dB.....	288
Appendix 22: Tabulation of the Theoretical Symbol Error Rate versus Expected SNR with no MAI for STS-TH-UWB-PPM system.....	289
Appendix 23: Tabulation of Theoretical Symbol Error Rate versus Expected SNR with 5 MAI sources each with an actual SNR of 64dB (expected SNR of 10dB) for STS-TH-UWB-PPM system .....	290
Appendix 24: Tabulation of Theoretical Symbol Error Rate versus Expected SNR with 10 MAI sources each with an actual SNR of 64dB (expected SNR of 10dB) for STS-TH-UWB-PPM system .....	291
Appendix 25: Plots of BER versus Eb/No for different spreading sequence sets with 95% confidence interval error bars for 5 and 10 MAI for STS-TH-UWB-PPM system .....	292
L=1 5 MAI BER versus measured Eb/No (dB) plots.....	292
L=4 5 MAI BER versus measured Eb/No (dB) plots.....	293
L=1 10 MAI BER versus measured Eb/No (dB) plots.....	294
L=4 10 MAI BER versus measured Eb/No (dB) plots.....	295
Appendix 26: Relationship between Expected SNR and measured Eb/No for simulations using database excell spreadsheet .....	296

## List of Figures

Figure 2.2-1: transmit receive setup for space-time diversity reproduced from [10].	9
Figure 2.4-1: MMRC setup from [14].	17
Figure 2.4-2: proposed system in [14].	18
Figure 2.4-3: Two by two setup from [14].	20
Figure 2.5-1: Proposed Space Time Spreading setup from [9].	29
Figure 2.9-1: Optimum receiver for orthogonal M-ary PPM with TH as reproduced from [44].	47
Figure 2.9-2: Multichannel MAC operation as reproduced from [6]	48
Figure 2.10-1: Results of BER performance versus SNR for single and multiple antenna Analog Coding Type I and II reproduced from [8].	66
Figure 2.10-2: Results of BER performance versus SNR for single and multiple antenna Analog ST Coding Type I scheme using $L=1$ for PPM reproduced from [8].	66
Figure 2.10-3: Results of BER performance versus SNR for single and multiple antenna Analog ST Coding Type I scheme using $L=4$ for PPM reproduced from [8].	67
Figure 2.11-1: Plan of floor used in measurements of radar-pulse like communication upon which Saleh-Valenzuela statistical model is based, reproduced from [7].	68
Figure 2.11-2: Shows the measurement setup used in 1987 to develop the Saleh-Valenzuela model as reproduced from [7].	69
Figure 2.11-3: Some sample averaged power profiles observed and reproduced from [7].	71
Figure 2.11-4: Figure reproduced from [7] which shows an envelope and ray representation of their proposed model.	75
Figure 2.11-5: averaged power profiles reproduced from [7].	77
Figure 3.2-1: (a) The computations done on $b_1$ and $b_2$ before being transmitted on $t_1$ and $t_2$ antennas [9]. (b) Shows complex fading coefficients for STS system.	82
Figure 3.3-1: Space Time Spreading Simulink Model.	84
Figure 3.3-2: Splitting streams into odd and even components.	84
Figure 3.3-3: Spreading stage of simulation.	85
Figure 3.3-4: Single path modeling STS channel.	88
Figure 3.3-5: Generation of Rayleigh pdf.	88
Figure 3.3-6: despreading with normalisation gain element.	89
Figure 3.3-7: Symbol Matched Filter, Integration done at actual symbol rate.	89
Figure 3.3-8: STS Decoder sub system.	89
Figure 3.4-1: Plot for $m=1$ and $m=2$ with perfect knowledge of the flat fading complex coefficients and no multipath for BPSK system using Simulink.	91
Figure 3.4-2: Plot for $m=1, 2, 4$ and $8$ with perfect knowledge of the flat fading complex coefficients and no multipath for BPSK system using Simulink with 95% confidence intervals for $m=4$ and $m=8$ cases [presented to Warsaw university April-May 2004]. (See Appendix 5 for the MATLAB scripts used).	92
Figure 4.1-1: A cell sectorised into three 120 degree segments [1].	96
Figure 4.4-1: System with scatter in Sector 2 producing MAI in Sector 1.	99
Figure 4.5-1: Effect of MAI on an adjacent sectors CDMA based user with User 1 received strength constant at 0dB, User 2 signal varies (single seed set used only).	100
Figure 4.5-2: Effect of MAI on an adjacent sectors CDMA based user with User 1 received strength constant at 4dB, User 2 signal varies (single seed set used only).	100

Figure 4.8-1: Bit Error Rate versus Expected SNR from User 2's signal at User 1's receiver comparing the results from Section 4.5 and those obtained using the improved Modified Walsh Hadamard codes proposed in [61].	102
Figure 5.2-1: Squared value of second derivative of Gaussian pulse.	108
Figure 5.2-2: Time plot of second derivative of Gaussian pulse.	109
Figure 5.2-3: Snap shot of a single channel over 100ns.	109
Figure 5.3-1: Selecting the Channel in Simulink.	111
Figure 5.4-1: Main communication link in simulator.	112
Figure 5.5-1: Comparison of measurements from Simulink model to estimates from Figures 7	113
Figure 5.5-2: BER versus Expected SNR (dB) for first arriving ray, first useful (PRake) arriving ray and strongest arriving ray (SRake) for Simulink Simulation.	114
Figure 5.5-3 : BER versus Expected SNR (dB) for the case first 4 arriving rays, first 4 useful (PRake) arriving rays and strongest 4 arriving rays (SRake) for Simulink Simulation.	114
Figure 5.5-4: Plot of a single seed for L=4 showing an error floor appearing after 28dB in Simulink Simulation.	115
Figure 5.5-5: Snapshot of a small segment of channel signal at the point where error occurs without any noise.	117
Figure 6.2-1: DS-TH-UWB simulations for two position PPM.	122
Figure 6.3-1: DS Modified-TH-UWB simulations for three position PPM 95% confidence intervals for this system are provided in Appendix 10.	123
Figure 6.4-1: Comparison of L=1 Partial Rake with DS-TH-UWB and DS-Modified-TH-UWB.	124
Figure 6.4-2: Comparison of L=4 Partial Rake using DS-TH-UWB and DS-Modified-TH-UWB.	125
Figure 6.4-3: Comparison of L=1 Selective Rake using DS-TH-UWB and DS-Modified-TH-UWB.	126
Figure 6.4-4: Comparison of L=4 Selective Rake using DS-TH-UWB and DS-Modified-TH-UWB.	126
Figure 7.2-1: DS-TH-UWB simulations for 2 position PPM for a single seed set.	131
Figure 7.3-1: STS Performance of MIMO TH-UWB-3 position PPM proposed chip based MRC (non-optimal).	134
Figure 7.5-1: Comparison of the SISO and MIMO technique for PRake, L=1.	135
Figure 7.5-2: Comparison of the SISO and MIMO technique for PRake, L=4.	136
Figure 7.5-3: Comparison of the SISO and MIMO technique for SRake, L=1.	137
Figure 7.5-4: Comparison of the SISO and MIMO technique for SRake, L=4.	138
Figure 8.4-1: Yang et al. results from [8] compared to Simulink implementation of [8] 's Analog ST coding I schema with Simulink simulation normalised.	147
Figure 8.5-1: Simulation of Analog ST coding I and STS-TH-UWB-PPM proposed system for Partial Rake L=1,4.	149
Figure 8.5-2: Simulation of Analog ST coding I and STS-TH-UWB-PPM proposed system for Selective Rake L=1,4.	149
Figure 8.5-3: Simulation of Analog ST coding I and STS-TH-UWB-PPM per antenna branch proposed system for Partial Rake L=1,4.	150
Figure 8.5-4: Simulation of Analog ST coding I and STS-TH-UWB-PPM per antenna branch proposed system for Selective Rake L=1,4.	150
Figure 9.4-1: Shows the effect of one MAI interferer offset by randomly varied time to desired STS-TH-UWB-PPM system for L=1 when interferer has $E_b/N_0$ of -26.8dB, using the same seed set value for the channel and noise sources.	156

Figure 9.4-2: Shows the effect of one MAI interferer offset by randomly varied time to desired STS-TH-UWB-PPM system for L=1 when interferer has $E_b/N_o$ of -16.8dB, using the same seed set value for the channel and noise sources. ....	156
Figure 9.4-3: Shows the effect of one MAI interferer offset by randomly varied time to desired STS-TH-UWB-PPM system for L=1 when interferer has $E_b/N_o$ of -6.8dB, using the same seed set value for the channel and noise sources. ....	157
Figure 9.4-4: Shows the effect of one MAI interferer offset by randomly varied time to desired STS-TH-UWB-PPM system for L=1 when interferer has $E_b/N_o$ of +3.15dB using the same seed set value for the channel and noise sources. ....	157
Figure 9.4-5: Shows the effect of five MAI interferers offset by randomly varied time to desired STS-TH-UWB-PPM system for L=1 and L=4 when all interferers have $E_b/N_o$ of -26.8dB using the same seed set value for the channel and noise sources. ....	158
Figure 9.4-6: Shows the effect of five MAI interferers offset by randomly varied time to desired STS-TH-UWB-PPM system for L=1 and L=4 when all interferers have $E_b/N_o$ of -16.8dB using the same seed set value for the channel and noise sources. ....	159
Figure 9.4-7: Shows the effect of five MAI interferers offset by randomly varied time to desired STS-TH-UWB-PPM system for L=1 and L=4 when all interferers have $E_b/N_o$ of -6.8dB using the same seed set value for the channel and noise sources. ....	159
Figure 9.4-8: Shows the effect of five MAI interferers offset by randomly varied time to desired STS-TH-UWB-PPM system for L=1 and L=4 when all interferers have $E_b/N_o$ of +3.15dB using the same seed set value for the channel and noise sources. ....	160
Figure 9.4-9: Shows the effect of ten MAI interferers offset by randomly varied time to desired STS-TH-UWB-PPM system for L=1 and L=4 when all interferers have $E_b/N_o$ of -26.8dB using the same seed set value for the channel and noise sources. ....	161
Figure 9.4-10: Shows the effect of ten MAI interferers offset by randomly varied time to desired STS-TH-UWB-PPM system for L=1 and L=4 when all interferers have $E_b/N_o$ of -16.8dB using the same seed set value for the channel and noise sources. ....	161
Figure 9.4-11: Shows the effect of ten MAI interferers offset by randomly varied time to desired STS-TH-UWB-PPM system for L=1 and L=4 when all interferers have $E_b/N_o$ of -6.8dB using the same seed set value for the channel and noise sources. ....	162
Figure 9.4-12: Shows the effect of ten MAI interferers offset by randomly varied time to desired STS-TH-UWB-PPM system for L=1 and L=4 when all interferers have $E_b/N_o$ of +3.15dB using the same seed set value for the channel and noise sources. ....	162
Figure 9.4-13: Shows the effect of five MAI interferers offset by randomly varied time to desired STS-TH-UWB-PPM system for L=1 and L=4 when all interferers have $E_b/N_o$ of +3.15dB with 95% confidence intervals. ....	163
Figure 9.4-14: Shows the effect of ten MAI interferers offset by randomly varied time to desired STS-TH-UWB-PPM system for L=1 and L=4 when all interferers have $E_b/N_o$ of +3.15dB with 95% confidence intervals. ....	163
Figure 9.5-1: Comparison of performance of wysocki codes, orthogonal gold codes, w32dash03 codes, h32dash03 codes versus Walsh Hadamard codes in the presence of five MAI interferers at +3.15dB for L=1 of mean BER versus Measured $E_b/N_o$ (dB). ....	166
Figure 9.5-2: Comparison of performance of wysocki codes, orthogonal gold codes, w32dash03 codes, h32dash03 codes versus Walsh Hadamard codes in the presence of ten MAI interferers at +3.15dB for L=1 of mean BER versus Measured $E_b/N_o$ (dB). ....	167

Figure 9.5-3: Comparison of performance of wysocki codes, orthogonal gold codes, w32dash03 codes, h32dash03 codes versus Walsh Hadamard codes in the presence of five MAI interferers at +3.15dB for L=4 of mean BER versus Measured $E_b/N_o$ (dB). .....	168
Figure 9.5-4: Comparison of performance of wysocki codes, orthogonal gold codes, w32dash03 codes, h32dash03 codes versus Walsh Hadamard codes in the presence of ten MAI interferers at +3.15dB for L=4 of mean BER versus Measured $E_b/N_o$ (dB). .....	168
Figure 9.5-5: Comparison of performance of orthogonal gold codes, w32dash03 codes, and Walsh Hadamard codes in the presence of five MAI interferers at +3.15dB for L=1 of mean BER versus Measured $E_b/N_o$ (dB). .....	170
Figure 9.5-6: Comparison of performance of orthogonal gold codes, w32dash03 codes, and Walsh Hadamard codes in the presence of ten MAI interferers at +3.15dB for L=1 of mean BER versus Measured $E_b/N_o$ (dB). .....	170
Figure 9.5-7: Comparison of performance of orthogonal gold codes, w32dash03 codes, and Walsh Hadamard codes in the presence of five MAI interferers at +3.15dB for L=4 of mean BER versus Measured $E_b/N_o$ (dB). .....	171
Figure 9.5-8: Comparison of performance of orthogonal gold codes, w32dash03 codes, and Walsh Hadamard codes in the presence of ten MAI interferers at +3.15dB for L=4 of mean BER versus Measured $E_b/N_o$ (dB). .....	171
Figure 10.2-1: Shows relationship between terms used to describe a STS-TH-UWB-PPM system. ....	174
Figure 10.5-1: Symbol Error Rate versus Expected SNR (dB) for all rake of an STS-TH-UWB-PPM system. ....	198
Figure 10.5-2: Symbol Error Rate versus Expected SNR (dB) for all rake in the presence of 5 MAI sources with expected SNR of 10dB of an STS-TH-UWB-PPM system. ....	199
Figure 10.5-3: Symbol Error Rate versus Expected SNR (dB) for all rake in the presence of 10 MAI sources with expected SNR of 10dB of an STS-TH-UWB-PPM system. ....	199
Figure 10.5-4: Symbol Error Rate versus Expected SNR (dB) for all rake in the presence of no MAI, 5 MAI and 10 MAI sources with expected SNR of 10dB of an STS-TH-UWB-PPM system. ....	200

## List of Tables

Table 2.2.1: A summary of the schemes for Real and Complex symbols for different values of $m$ , adapted from a similar table shown in [10].....	13
Table 3.4.1: Measured values from $m=1$ Simulink simulation of Space Time Spreading System .....	90
Table 3.4.2: Measured values from $m=2$ Simulink simulation of STS System.....	92
Table 5.5.1: Data used to form the channel around the location of the error.....	116
Table 7.3.1: Sample of Space Time Spreading codes shown for individual chip level values for a 32 chip spreading sequences $c_1$ and $c_2$ used in simulation when transmitting $\{-1,-1\}$ pairing. ....	133
Table 7.4.1: Measured $E_b/N_0$ calculations for MIMO STS UWB system.....	135

## List of Abbreviations

AWGN	Additive White Gaussian Noise
BER	Bit Error Rate
BPSK	Binary Phase Shift Keying
BS	Base Station
CDF	Cumulative Distribution Function
CDMA	Code Division Multiple Access
CFO	multicarrier offsets (carrier frequency offsets)
CSI	Channel State Information
DS	Direct Sequence
DSP	Digital Signal Processing
FCC	Federal Communications Commission
FET	Field Effect Transistor
FFT	Fast Fourier Transform
FH	Frequency Hopping
H-R	Hurwitz-Radon
ICI	Inter Carrier Interference
IEEE	Institution of Electrical and Electronic Engineers
IFFT	Inverse Fast Fourier Transform
ISDN	Integrated Services Digital Network
ISI	Inter-symbol Interference
IS-OFDM	Interference Suppressing OFDM
I-UWB	Impulse based Ultra Wideband
LAN	Local Area Network
MAC	Medium Access Control
MAI	Multiple Access Interference
M-ALOHA	Multi-channel ALOHA
Mcps	Mega chips per second
MFSK	M-ary Frequency Shift Keying
MIMO	Multiple Input Multiple Output
MMRC	Maximal Ratio Receiver Combining
MOFDM	Multiband OFDM
M-PSMA	multi-channel pulse sense multiple access
MRC	Maximum Ratio Combining

MS	Mobile Station
MUI	Multiple User Interference
NLOS	Non Line of Sight
OFDM	Orthogonal Frequency Division multiplexing
OFDMA	Orthogonal Frequency Division Multiple Access
OOK	On-off keying
OTD	Orthogonal Transmit Diversity
PA	Power Amplifier
PAM	Pulse Amplitude Modulation
PAPR	Peak to Average Power Ratio
pdf	probability density function
PG	Processing Gain
PPM	Pulse Position Modulation
PRF	Pulse Repetition Frequency
PRI	Pulse Repetition Interval
PSK	Phase Shift Keying
QPSK	Quadrature Phase Shift Keying
RTW	Real Time Workshop (from MATLAB/Simulink)
SDMA	Space Division Multiple Access
SER	Symbol Error Rate
SINR	Signal in Noise Ratio
SISO	Single Input Single Output
SNR	Signal to Noise Ratio
ST	Space Time
STS	Space Time Spreading
SV	Saleh-Valenzeula
TH	Time Hopping
UWB	Ultra Wideband
WCDMA	Wideband Code Division Multiple Access
WSN	Wireless Sensor Network